



## 3607515 - P-360 Aluminum tape w/liner

<b>Description</b>	Aluminum carrier with butyle adhesive.
<b>Product properties</b>	It consists of a aggressive butyle adhesive with a aluminum carrier and a white LDPE liner.
<b>Specifications</b>	<p>This tape provides instant water and air-tight seal and is resistant to moisture and solvents.</p> <p>It is used for permanent repairs and is very easy to use in tight spaces. The aluminum carrier and butyle adhesive conforms easily to round, square and odd-shaped objects.</p>
<b>Applications</b>	This product can be used for duct joint sealings for all HVAC systems. In addition to this it can be used for window and door flashing, repairing of aluminum sidings, sheet metals, gutters, storage buildings, flashing, containers and more. Furthermore it can be used for sealing roof alleys, eaves, hips and ridges.
<b>Storage and ageing</b>	3 years shelf life whilst stored in original packaging and 25C room temperature. Keep out of direct sunlight. Humidity conditions must be between 40-60%
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.
<b>Additional technical properties</b>	Tested in accordance to UL 723



## TECHNICAL DATA

<b>Carrier</b>	Aluminium	
<b>Adhesive</b>	Rubber butyl	
<b>Colour</b>	Aluminium	
<b>Liner</b>	PE film white	
<b>Weather resistant</b>	Yes	
<b>UV resistant</b>	Yes	
<b>Ageing resistant</b>	Yes	
<b>Thickness Carrier</b>	0,051 mm	2,01 Mils
<b>Thickness Total</b>	0,889 mm	35 Mils
<b>Adhesion on stainless steel</b>	9 N/25mm	2,06 Lbs/inch
<b>Tensile strength length</b>	88 N/25mm	20,1 Lbs/inch
<b>Tensile strength width</b>	88 N/25mm	20,1 Lbs/inch
<b>Service temperature</b>	Between 4 and 93 °C	Between 39,2 and 199 °F
<b>Application temperature</b>	Between 4 and 93 °C	Between 39,2 and 199 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.